



# LUBRA-GLIDE (F, C) LUBRICANT

PRODUCT  
DATA

**LUBRA-GLIDE** is a powdered lubricant available in two grades: Fine and Coarse.

## TYPICAL USES:

- Spot in hole prior to running casing or liners.
- Spot in hole prior to logging operations.
- Allows more true weight to bit.
- Spot in key seats to reduce torque, drag and sticking problems.
- Apply LUBRA GLIDE FINE for torque and drag in coil tubing operations or with work strings.
- Lubricant for OBM or SBM.
- Aids in prevention of differential sticking when using OBM / SBM.
- Aids in directional changes or sliding.

## FEATURES AND BENEFITS:

- Reduces torque and drag, casing wear.
- Is non-abrasive and environmentally safe
- Is recoverable using a patented process.
- Is thermally stable to 260°C.
- Is compatible with both oil- and water-based mud
- Resistance to deformation is > 25,000 psi hydrostatic
- Thermally stable down hole to 260°C in a drilling environment.

## RECOMMENDED TREATMENT:

To control torque and drag: 5.7 - 22.97 kg/m<sup>3</sup>

For spotting wire-line and casing operations: 22.9 – 34.3 kg/m<sup>3</sup>

## PHYSICAL PROPERTIES:

Appearance:	White powder
Specific Gravity:	1.06
Solubility:	Insoluble

## MIXING/HANDLING:

Mix through a conventional mud hopper. Refer to the MSDS for specific precautions and handling requirements.

**MICROTOX<sup>®</sup> THRESHOLD: TBD**

**PACKAGING: 22.68 kg bag / 40 bags/pallet**



Right product. Right place. Right time.

[www.brichem.com](http://www.brichem.com) 403.252.5904

**BRI-CHEM**  
SUPPLY LTD