

SAFETY DATA SHEET

SUN BURST DP®

1. Identification

Product Name: Sun Burst DP®
Effective Date: March 01, 2016
Chemical Family: Drilling Fluid Additive
Usage: Friction Reducer
Manufacturer: Sun Drilling Products Corp.
503 Main Street
Belle Chasse, LA 70037
(504)393-2778

Emergency phone number CHEMTREC USA/Canada 1-800-424-9300
Outside USA/Canada 1-703-527-3887

Recommended restrictions While it is unlikely during expected usage that airborne respiratory hazards will be present, workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Carcinogenicity. Category 1A
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement May cause cancer.

Precautionary statement Eye contact may cause severe eye irritation. Prolonged and repeated exposure to excessive concentrations of this product's dust containing <0.3% quartz, or any nuisance dust, can cause chronic pulmonary disease. Long term exposure may cause silicosis. The NTP (National Toxicology Program) and IARC (International Agency for Research on Cancer) has determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. A single exposure under normal conditions of use will not result in serious adverse effects.

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store in dry location.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information None.

3. Composition/information on ingredients

Chemical name	CAS#	%
Polystyrene Sulphonic Acid	69011-20-7	50-60
Mixture of C16-C18 Methyl Esters from Vegetable Oils		5-15
Diatomaceous Earth, Natural	61790-53-2	0.25-0.5
Contains < 1% Silica, Quartz	14808-60-7	
Graphite	7782-42-5	1-2
Contains < 0.1% Respirable Silica, Quartz	14808-60-7	
Talcum Powder	14807-96-6	0.1-0.25
Contains < 1% Silica, Quartz	14808-60-7	

4. First-aid measures

Most important symptoms/effects, acute and delayed

Dusts may irritate the respiratory tract, skin and eyes.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion Rinse mouth. Get medical attention if symptoms occur.
General information If exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Firefighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Firefighting equipment/instructions Use water spray to cool unopened containers.
Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of

spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Collect dust using a vacuum cleaner equipped with HEPA filter.

Environmental precautions

Avoid discharge of product into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation for operations/locations where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment.
Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in secure location. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

TLV: 8 hr Time Weighted Avg (TWA): 0.025 mg/m³, respirable fraction. /Silica, Crystalline - alpha-Quartz (14808-60-7, 1317-95-9); and Cristobalite (14464-46-1)

American Conference of Governmental Industrial Hygienists TLVs and BEIs. Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices. Cincinnati, OH, 2008, p. 51

Diatomaceous Earth: OSHA PEL 5 mg/ m³ Respirable Dust, 15 mg/ m³ Total Dust

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye

Safety glasses or protective goggles to prevent eye contact.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other	Use of an impervious apron is recommended.
Respiratory protection	Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid
Form	Coated beads
Color	Gray-black
Odor	Mild
Odor threshold	Not available
pH	Neutral to slightly alkaline
Melting point/freezing point	Not applicable
Initial boiling point and boiling range	Not applicable
Flash point	>200 °F
Evaporation rate	Not applicable
Flammability (solid, gas)	Solid
Upper/lower flammability or explosive limits	Not available
Flammability Limit – lower (%)	Not available
Flammability Limit – upper (%)	Not available
Explosive limit – lower (%)	Not available
Explosive limit – upper (%)	Not available
Vapor pressure	Not applicable
Vapor Density	Not applicable
Relative Density	Not available
Solubility (ies)	Insoluble in organic solvents and acids
Solubility (water)	Insoluble
Partition Coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available

Decomposition temperature	Not available
Viscosity	Not applicable
Other Information	
Density	50 lbs/ft ³
Specific gravity	1.25-1.32

10. Stability and Reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical Stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Phosphorus. Maleic anhydride. Nitroethane. Fluorine. Nitromethane. Nitroparaffins. Chlorine. Nitropropane
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin.
Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause severe irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the

carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline Silica (CAS 14808-60-7)	1 Carcinogenic to humans.
Diatomaceous earth, natural (CAS 61790-53-2)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Silica (CAS 14808-60-7)	Known To Be Human Carcinogen.
-------------------------------------	-------------------------------

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects
Specific organ toxicity - Single exposure	Not classified.
Specific organ toxicity - Repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	The product is not considered to be toxic to aquatic organisms. A 96-hr. lethal concentration for bluegill of biodiesel grade methyl esters was greater than 1000 mg/L. Lethal concentrations at these levels are generally deemed "insignificant" according to NIOSH (National Institute for Occupational Safety and Health) guidelines in its <i>Registry of the Toxic Effects of Chemical Substances</i> .
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
------------------------------	--

Local disposal regulations	Dispose of in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residue. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization

Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline Silica (CAS 14808-60-7)

US. Massachusetts RTK - Substance List

Crystalline Silica (CAS 14808-60-7) Diatomaceous earth, natural (CAS 61790-53-2)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline Silica (CAS 14808-60-7) Diatomaceous earth, natural (CAS 61790-53-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline Silica (CAS 14808-60-7) Diatomaceous earth, natural (CAS 61790-53-2)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline Silica (CAS 14808-60-7)

Listed: October 1, 1988

Australia	Australian Inventory of Chemical Substances (AICS)
Canada	Domestic Substances List (DSL)
Canada	Non-Domestic Substances List (NDSL)
China	Inventory of Existing Chemical Substances in China (IECSC)
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)
Europe	European List of Notified Chemical Substances (ELINCS)
Japan	Inventory of Existing and New Chemical Substances (ENCS)
Korea	Existing Chemicals List (ECL)
New Zealand	New Zealand Inventory
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

03-01-2016

Version #

01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.